


**EGESERAMİK** PACKING AND TECHNICAL SPECIFICATIONS

SIZE	TYPE	PEI VALUE	WET (COF'S)	DRY (COF'S)	WATER ABSORPTION	SCRATCH HARDNESS (MOH'S)	SHADE VARIATION (CTDA)	BREAKING STRENGTH (LBF)	CHEMICAL RESISTANCE
10x13	wall tile	-	-	-	18.40%	5	v3	179.7	resistant
13x13	glazed porcelain	4	0.60-0.65	0.70-0.75	0.39%	6	v3	360	resistant
18x18	glazed porcelain	4	0.60-0.65	0.70-0.75	0.28%	6	v3	384	resistant

SIZE	TYPE	LBS/PCE	PCS/BOX	LBS/BOX	BOX/PLT	SQ.FT/BOX	SQ.FT/PLT	NET LBS/PLT	GROSS LBS. PLT	PLT/CTN 20FT.	LBS/CTN 20FT.	SQ.FT/CTN 20FT.	PALLET HEIGHT (31x47x...)
10x13	wall tile	2.535	12	30.42	69	10.76	742.71	2,099.24	2,143	22	47,153.36	16,340	35.83
13x13	glazed porcelain	4.17	9	37.52	62	10.76	667.36	2,326.41	2,370.50	20	47,409.98	13,347.25	31.89
18x18	glazed porcelain	8.55	7	59.88	52	15.26	793.41	3,113.63	3,157.73	15	47,365.88	11,901.12	41.73