


EGE SERAMİK PACKING AND TECHNICAL SPECIFICATIONS

SIZE	TYPE	PEI VALUE	WET (COF'S)	DRY (COF'S)	WATER ABSORPTION	SCRATCH HARDNESS (MOH'S)	SHADE VARIATION (CTDA)	BREAKING STRENGTH (LBF)	CHEMICAL RESISTANCE
6x18	wall tile	-	-	-	16.80%	6	v2	211	resistant
12x18	wall tile	4	0.60-0.65	0.70-0.75	16.80%	6	v2	211	resistant
13x13	modular	3	0.60-0.65	0.73-0.78	0.26%	8	v2	400	resistant
18x18	glazed porcelain	3	0.60-0.65	0.73-0.78	0.29%	8	v2	459	resistant

SIZE	TYPE	LBS/PCE	PCS/BOX	LBS/BOX	BOX/PLT	SQ.FT/BOX	SQ.FT/PLT	NET LBS/PLT	GROSS LBS. PLT	PLT/CTN 20FT.	LBS/CTN 20FT.	SQ.FT/CTN 20FT.	PALLET HEIGHT (31x47x...)
6x18	wall tile	2.646	10	26.46	64	7.27	465	1,693.15	1,737	27	46,905.56	12,555	29.92
12x18	wall tile	5.049	8	40.39	48	11.63	558	1,938.66	1,983	23	45,603.24	12,834	29.92
13x13	modular	4.59	18	21.03	112	5.38	602.78	2,355.60	2,399.69	19	45,594.07	12,012.52	31.89
18x18	glazed porcelain	8.55	7	59.88	52	15.26	793.41	3,113.63	3,157.73	15	47,365.88	11,901.12	41.73